



Power Fluids PF-1™ is an engineered extreme pressure lubricant that starts where motor oil leaves off, by conditioning the metal of your engine, without changing the viscosity or manufacturer's lubrication formula. This is accomplished by smoothing the microscopic irregularities, cracks and points of uneven wear on the surface of bearings, pushrods, lifters, crank and cam shafts and all internal moving parts that oil is pumped to, are conditioned.

Power Fluids PF-1™ creates a smooth, oiled surface that greatly reduces friction in all areas of metal to metal contact. The reduction of friction significantly reduces heat and wear, which extends component service life and lessens maintenance costs and down time. The reduction of heat and wear in moving parts creates less sludge, gum and varnish due to oil breakdown or a lack of maintenance.

Power Fluids PF-1™ cleaning action breaks down sludge build up so it can be drained during an oil change – any oil that comes out clean is not cleaning your engine. The dirty oil is being

deposited as sludge build up within the engine and, left un-checked, can slow or clog oil returns and cause lifters to work improperly.

Power Fluids PF-1™ is engineered to blend with petroleum and synthetic oils, gear lubes, transmission fluids and grease. It contains no solids to retard penetration and will not cause any material build up or change even the finest of machine tolerances. Used in conjunction with Power Fluids' other fine products, your vehicle's engine will perform at peak levels while generating increased cost of fuel savings to you.

Power Fluids PF-1™ contains no Chlorine, Teflon, Zink, Molybdenum, or other solids of any kind.

BENEFITS :

- Improves fuel mileage**
- Eliminates "dry" starts**
- Prolongs the life of the engine, transmission, gear box and differential**
- Protects the moving metal parts against friction and heat**
- Increases acceleration, horsepower, torque and performance**
- Penetrates the metal surface to form a polished shield that reduces friction**
- Removes accumulated contaminants, keeps lifters working properly**

USAGE DIRECTIONS

GAS & DIESEL ENGINES up to 8 quarts, add one 8-ounce bottle Power Fluids PF-1™ every 15,000 miles and transmission every 24,000 miles.

LARGER ENGINES See directions on bottle

Other Applications:

Apply one ounce of PF-1 to every 16 oz. of lubricant every 500 hours in engines/drivers and every 1000 hours in compressors, transmissions and hydraulic systems. Contact your dealer for further details.